

# Circuit-Lock® 30A Disconnects with LED INDICATORS



Hubbell’s new 30A Circuit-Lock Disconnect with integral phase indication LEDs redefines the benchmark for safety by providing insight into the enclosure while in use.

The voltage detection feature significantly improves existing safety and maintenance procedures by visually providing personnel critical information prior to removing the enclosure cover; e.g. a welded contact or dropped phase. Six highly visible LEDs (3 line side/3 load side) show the electrical status of the switch by phase.

Hubbell inSIGHT™ phase indicating disconnect switches are available in non-metallic and stainless steel versions. Replacement covers are available for upgrades to existing installations. With an ever

growing focus on safety improvements, Hubbell inSIGHT™ disconnects provide a difference you literally can see.



[View Hubbell inSight Disconnects](#)



- Features**
- Six highly visible integral phase identification LEDs
  - External LEDs provide a surface visual confirmation of make/break on all phases
  - Cover cannot be removed with switch in the “ON” position
  - Certified by NSF for hygiene in Food Processing applications
  - Highly visible red handle that meets OSHA LO/TO capabilities
  - Available in 30A non-metallic & stainless steel versions, with or w/o JOG switch
  - UL witnessed IP69k and UL Type 4X and 12 Environmental ratings

**Rating Information**  
Water & Dust Ingress Protection

**IP69 Water Test**  
Extremely Hot (176°) and High Pressure Water (1450 psi) sprayed from various angles.

**IP69 Dust Test**  
Device is placed in a dust chamber for 8 hours while a vacuum tries to pull dust into the sealed device.

**National Sanitation Foundation (NSF)**  
Known as The Most Trusted Name in Food Safety™, NSF International has been helping businesses in the agriculture, processing, food equipment, restaurant and retail industries to navigate the food safety and regulatory environment for nearly 70 years.

## 30A UNFUSED DISCONNECT SWITCHES WITH LEDS

**Non-Metallic**



**HBLDS3P**

(w/Jog Switch)

**HBLDS3PJ**

Replacement Cover

**HBLDS3RCP**

**Stainless Steel Square Top**



**HBLDS3SSP**

Replacement Cover

**HBLDS3SSRCP**

**Stainless Steel Sloped Top**



**HBLDS3SSRP**

(w/Jog Switch)

**HBLDS3SSRPJ**

Replacement Cover

**HBLDS3SSRRCP**

## AUXILIARY CONTACTS

“Break After Main Break”, 1 set of n/o contacts, 1 set of n/c contacts

**HBLAC1**

“Break Before Main Break”, 1 set of n/o contacts for use with variable frequency drives

**HBLAC1**

For more info about Hubbell inSIGHT Disconnects call **1-800-STEINER** (783-4637) to speak with a Steiner application engineer.

**STEINER**  
www.steinerelectric.com

